

imageRUNNER
ADVANCE DX
C5760i/C5750i
C5740i/C5735i

imageRUNNER ADVANCE DX C5700 Series

Print up to 60 ppm (BW/color)

Scan up to 270 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

6,350-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE DX multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.





WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder and automatically print with pre-defined settings such as number of copies and finishing requirements.
- * Security Information and Event Management



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*.² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control³ utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.





DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold5

CONFIGURATION OPTIONS



STAPLE FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



BOOKLET FINISHER-Y1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



INNER FINISHER-H1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets within the footprint of the main unit
- Supports Staple-free* Stapling and Staple on Demand
- Supports optional internal 2/3-hole puncher (Inner 2/3 Hole Puncher-B1)



INNER 2-WAY TRAY





HIGH CAPACITY CASSETTE FEEDING UNIT-A1

- 2,450-sheet capacity
- Supports up to Letter
- 14 lb. Bond to 140 lb. Index



CASSETTE FEEDING UNIT-AM1

- Two 550-sheet cassettes
- Supports up to 12" x 18"
- 14 lb. Bond to 140 lb. Index







COPY TRAY-J2



PAPER DECK UNIT-F1

- 2,700-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports Letter



imagePASS-P2 v1.1

- Delivers fast processing speed, outstanding image quality, and timesaving workflow
- Personalized printing with the built-in, entrylevel Fiery FreeForm™ or with the supported variable data printing (VDP) formats

SPECIFICATIONS

Main Unit

Type

Color Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store Standard:

Optional:

Processor

1.75GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory 4.0 GB RAM

Hard Disk Drive

Standard: 250 GB/Maximum: 1 TB

Interface Connection

1000Base-T/100Base-TX/10Base-T, Network Wireless LAN (IEEE 802.11 b/g/n) Others

USB 2.0 (Host) x1, USB 3.0 x1 (Host), Standard: USB 2.0 x1 (Device)

Serial Interface, Copy Control Interface Optional:

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets 3,450 Sheets Maximum:

(with External Finisher and Copy Tray)

Paper Sources (LTR, 20 lb. Bond)

Dual 550-sheet Paper Cassettes, Standard:

100-sheet Stack Bypass

Optional: Dual 550-Sheet Paper Cassettes (Cassette Feeding Unit-AM1), 2,450-Sheet

High Capacity Paper Cassette (High Capacity Cassette Feeding Unit-A1), 2,700-Sheet Paper Deck

(Paper Deck Unit-F1) Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets 6.350 Sheets Maximum: **Finishing Capabilities**

Standard: Collate, Group

Collate, Group, Offset, Staple, Saddle-Stitch, With Options:

Hole Punch, Eco Staple, Staple On Demand

Supported Media Types

Multi-Purpose Thin, Plain, Recycled, Color, Heavy, Coated, Tracing, Bond, Transparency, Label, Tray Pre-punched, Letterhead, Tab, Envelope

Paper Thin, Plain, Recycled, Color, Heavy, Bond, Cassettes: Transparency, Pre-punched, Letterhead,

Envelope6

Supported Media Sizes

Upper Letter, Executive, Statement-R, Envelope [No.10 (COM10), DL, ISO-C5], Custom Size Cassette: (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2") 12" x 18", 11" x 17", Legal, Letter, Letter-R, Lower

Cassette: Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5] Custom Size (3-7/8" x 7-1/8" to 12" x 18")

Multi-Purpose 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Tray: Envelope [No.10 (COM10), Monarch, DL,

ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size/ Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²) Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²) 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) Duplexing:

Print/Copy Speed (BW and Color)

Up to 60 ppm (Letter); Up to 36 ppm C5760i:

(Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")

Up to 50 ppm (Letter); Up to 30 ppm C5750i: (Letter-R); Up to 29 ppm (Legal);

Up to 27 ppm (11" x 17")

C5740i: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal);

Up to 22 ppm (11" x 17

Up to 35 ppm (Letter); Up to 23 ppm C5735i: (Letter-R); Up to 21 ppm (Legal);

Up to 18 ppm (11" x 17")

Warm-up Time

From Power Approx. 10 Seconds⁷

On: From Sleep Approx. 10 Seconds8

Mode:

Quick Startup Approx. 4 Seconds⁹

Mode:

Dimensions (W x D x H)

24-3/8" x 28-1/2" x 36-7/8" (620 x 722 x 937 mm)¹⁰

Installation Space (W x D)

42-5/8" x 45-3/4" (1,083 x 1,162 mm) Basic:

(Right Cover Open with Multi-purpose tray extended + Cassette Drawers Open) 73-1/2" x 45-3/4" (1,866 x 1,162 mm)

Fully (Booklet Finisher-Y1 with the extension Configured: tray extended + Paper Deck Unit-F1 +

Cassette Drawers open)

Approx. 310.9 lb. (141 kg)11

Print Specifications

Print Resolution (dpi)

1200 x 1200

Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

Supported File Types

PDF, TIFF, JPEG, EPS, 12 XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts

PCL:

PPD:

93 Roman, 10 Bitmap fonts, 2 OCR fonts, PCL: Andalé Mono WT J/K/S/T (Japanese,

Korean, Simplified and Traditional Chinese), 13 Barcode Fonts¹⁴

136 Roman

Operating System¹⁵

UFRII/PS: Windows® 7/8.1/10/Server2008/

Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X

(10.10 or later) Windows® 7/8.1/10/Server2008/

Server2008 R2/Server2012/Server2012

R2/Server2016/Server2019 Windows® 7/8.1/10, Mac OS X(10.9 or later)

Copy Specifications

First-Copy-Out Time

C5760i: As fast as 2.9 seconds (BW)/ 4.5 seconds (Color)

As fast as 3.5 seconds (BW)/ C5750i:

5.2 seconds (Color) As fast as 4.1 seconds (BW)/

6.1 seconds (Color) As fast as 4.9 seconds (BW)/ C5735i:

7.4 seconds (Color)

Copy Resolution (dpi) 600×600

C5740i:

Multiple Copies

Up to 999

Magnification

25%-400% (1% Increments)

Preset Reductions/Enlargements 25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%,

200%, 400%

Scan Specifications

Single-Pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

Up to 200 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,

Custom Size: 2-3/4" x 5-1/2" to 12" x 17"

Document Feeder Supported Media Weights

Single-Sided 13.3 lb. Bond to 80 lb. Cover (50 to 220 gsm) Scanning: (BW, CL)
Double-Sided 13.3 lb. Bond to 80 lb. Cover (50 to 220 gsm)

Scanning (BW.CL)

Platen Acceptable Originals Sheet, Book, 3-Dimensional Objects

Pull Scan

Color Network ScanGear2 for both Twain and WIA Supported Windows® 7/8.1/10/Server 2008/ Supported Server 2008 R2/Server 2012/

Server 2012 R2/Server 2016

Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/

ÎFAX), (Pull) 600 x 600

Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to compatible mobile devices and certain cloud-based services depending on your requirements.

Scan Speed (LTR) (BW/CL)

Single-sided

135/135 (300 dpi), 80/80 (600 dpi),

Scanning: Double-sided

270/270 (300 dpi), 160/90

Scanning: (600 dpi)

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP,

WebDAV, Mail Box Super G3 FAX, IP Fax

Optional: Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Up to 600 x 600 Push: Pull-Up to 600 x 600

Communication Protocol

FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV

SMTP, POP3

File Format

Standard:

TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, User Signature, PDF A/1-b, Limited Color, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature,

User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications (Optional)

Modem Speed

Super G3: 33.6 Kbps G3: 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses **Memory Backup**

Yes

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 8.1/10)

Concurrent Connections (Max.)

SMB: 64 WebDAV: 3

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD) Approx. 480 GB (With Optional 1 TB HDD)

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online

Express,¹⁶ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup,³ McAfee Embedded Control³

Hard Disk Drive Mirroring, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Optional:

Standard: Encrypted Secure Print, IP/Mac

Address Filtering, IPsec, TLS Encrypted Communication (vl.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5

Integration, Encrypted PDF, Encrypted Secure Print, Digital Signature

User Signature

Environmental Specifications

Operating Environment Temperature: 50 to 86° F

Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements

C5760i/

C5750i: 110-127V, 60Hz, 11.5A C5740i/ C5735i: 110-127V, 60Hz, 10A

Power Consumption

Maximum: Approx. 1,800 W Standby: Approx. 63.1 W¹⁷ Sleep Mode: Approx. 0.8 W¹⁸

Sleep Mode: Approx. 0.8 W^{I8}
Typical Electricity Consumption (TEC) Rating^{I9}

C5760i: 0.84 kWh C5750i: 0.68 kWh C5740i: 0.57 kWh C5735i: 0.47 kWh

Standards

ENERGY STAR® Certified Rated EPEAT® Gold⁵

Consumables

Toner

GPR-55 Toner²⁰

Toner Yield (Estimated @ 5% Coverage)
Black: 69,000 Images
Color (C,M,Y): 60,000 Images

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.

² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.

³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

4 Requires additional option.

⁵ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁶ Envelope Feeder Attachment (standard) is required.

⁷ Time from device power-on, until copy ready (not print reservation).

8 Time from exiting Sleep mode to when printing is operational.

⁹ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

¹⁰ Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-AI, or Cabinet Type-N.

Il Includes main unit, consumables, and Cassette Feeding Unit-AMI

¹² EPS can be printed directly only from the Remote User Interface.

¹³ Requires the optional PCL International Font Set-A1.

14 Requires the optional Barcode Printer Kit-D1.

Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

16 No charge for this solution; however, activation is required.

¹⁷ Reference Value (measured one unit).

¹⁸ 0.8 W Sleep mode not available in all circumstances due to certain settings.

¹⁹ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

²⁰ GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images













As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imagePASS, and the GENUINE good are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks of the security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America sales representative for details. Product shown with optional accessories. Canon U.S.A. and Canon Solutions America do not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability to dange without notice. Not responsible for typographical errors.

©2020 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc., Canon Solutions America, Inc., and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.











